

SONY®

Spec Sheet

This professional 4-head DAT recorder comes with a dependable 4-DD Mechanism, as well as Super Bit Mapping (SBM) recording functions.



(Rear Panel)

New

Digital Audio Tape Deck

PCM-2800

Features:

- 4-Head Construction for Confidential Monitoring
- 4 Direct Drive Motors in the Mechanical Deck—Eliminates the need for drive belts and improves the accuracy, stability and durability of the tape transport.
- SBM Recording Functions—Achieves exceptional sound quality with 20-bit resolution.
- Parallel Remote Port for Effective Feeder Starts
- Interface Options for Both Professional and Personal Use —
 - Digital AES/EBU, IEC 958 Type 1/2.
 - Analog Balanced (XLR), Unbalanced (RCA pin)

Specifications:

- Analog Input/Output: Balanced (XLR), Unbalanced (RCA Pin)
- Digital Input/Output: AES/EBU (XLR), IEC 958 Type 1/2 (Coaxial)
- Dimensions: Approx. 430 x 125 x 292mm (W x H x D)
Approx. 16-15/16 x 4-7/8 x 1-1/2in. (W x H x D)
- Weight: Approx. 13 lbs 11oz./6.2kg
- Supplied Accessories: Wireless remote commander (RM-D868), Rack mount adaptor

For more information call
1-800-635-SONY

©1995 Sony Electronics Inc. Sony Business and Professional Products Group 3 Paragon Drive, Montvale, NJ 07645-1735
A-0908